

The XAS 110


The XAS 110 is the result of over a decade of continuous development. This compressor is perfect for single tool applications (or two if the new RTEX breaker is used) and for sites with difficult access and terrain. This model is part of our legendary 8 Series range. The models in the 8 Series have three key things in common:

Lightweight: A footprint at least 10% more compact than any other option.

Service: Simplicity, speed and long service intervals.

Built better: More features as standard. Breaking new ground when it comes to efficiency. (12% fuel savings versus any 185 cfm compressor)

The result is a compressor which can produce 95 CFM without the need for any exhaust after treatment. The 8 Series ticks all the boxes when it comes to delivering outstanding performance in all of these categories.






Your single tool solution

The XAS 110 can power a 90 pound tool and a DCP 10 dust collector. A simple and efficient set-up, while guaranteeing compliance to OSHA's Respirable Crystalline Silica standard.

XAS 110 simple service



Technical data

Compressor		XAS 110
Actual free air delivery (FAD)	cfm	95
Normal effective working pressure	psi	100
Max. sound pressure level @ 23' (7m) at normal working speed and pressure	dB(a)	70
Air receiver capacity	US Gal	2.34
Compressor oil capacity	US Gal	1.98
Air compressor outlets		2 x ³/4"
Engine		
Engine model		Kubota D 902 T4F
Emissions regulation	US EPA	Tier 4 Final
Number of cylinders		3
Engine speed (Unloaded)	rpm	2000
Engine speed (Maximum loaded)	rpm	3600
Engine oil capacity	US Gal	0.95
Fuel tank capacity	US Gal	7.35
Fuel consumption at 100% load	Gal/Hr	1.32
Dimensions and weight (including undercarriage)		
Weight (inc. fuel)	lb	1100
Length	in	79
Width	in	48
Height	in	51

According to ISO 1217 ed.3 1996 annex D

Power Technique Solutions Portfolio

Atlas Copco's Power Technique Business Area has a forward-thinking philosophy. For us, creating customer value is all about anticipating and exceeding your future needs – while never compromising our environmental principles. Looking ahead and staying ahead is the only way we can ensure we are your long term partner.

Air compressors



- 95-250 cfm
- 58-150 psi

Versatility



- 400-900 cfm
- 58-200 psi
- *Diesel and electric options available

Productivity partner



- 950-1800 cfm
- 100-508 psi
- *1000-5000 psi with Boosters

Generators

Portable



Mobile

• 25-1200* kVA



• 1.6-12 kVA

Dewatering pumps

Electric submersible



Self-priming pumps

• up to 6,155 g/min



Light towers

Metal halide



LED



Photos and illustrations contained herein might depict products with optional and/or extra components which are not included with the standard version of the product and, therefore, are not included in a purchase of such product unless the customer specifically purchases such optional/extra components. We reserve the right to change the specifications and design of products described in this literature without notice. Not all products are available in all markets.



Atlas Copco Power Technique atlascopco.com/ptba