

CPS 250-150 Compressor

Portable. **Powerful.**
Tough.



Features:

- Controlled Pressure Technology, different pressure settings at only one compressor model
- 110% Spillage Free Containment Frame
- Spin on type compressor oil separator
- Redrock™ Enclosure
- Battery Cut-off switch
- 3-layer painting
- U Flex canopy design

Options:

- Aftercooler + Water Separator + Bypass valve
- Cold Start
- SKID mount

Compressor		CPS 250-150
Free air delivery (FAD) @ effective working pressure	cfm	238 - 214 - 189
Normal effective working pressure	psig	100 - 125 - 150
Maximum unloaded pressure	psig	150
Minimum working pressure	psig	72.5
Air compressor outlets		2 x 3/4" + 1x 1 1/2"
Max. sound pressure level (LPA) at 7m (23ft)	dB(A)	70
Max. ambient temperature at sea level	F (C)	113 (45)
Min. starting temperature (without cold start aid)	F (C)	14 (-10)
Min. starting temperature (with cold start aid) (*)	F (C)	-4 (-20)
Compressor oil	Gal (L)	3.0 (11.4)
Capacity fuel tank	Gal (L)	23 (87)
Fuel consumption @ 100% load	Gal/hr (L/hr)	3.43 (12.98)
Fuel autonomy at full load standard	hr	6.71
Engine		Kubota
Model		V2403-CR-T-E4B
Number of cylinders		4
Displacement	L	2.4
Power output @ normal shaft speed	hp	65
Emissions level		Tier 4 Final
Full load rpm	rpm	2700
Unload rpm	rpm	1800
Trailer undercarriage dimensions		
Length x width x height	Inches	148 x 62.7 x 63.4
Weight (wet)	lbs (kg)	2566 (1164)
SKID dimensions (*)		
Length x width x height	Inches	117 x 71.2 x 69.1
Weight (wet)	lbs (kg)	2423 (1099)

(*) Optional

People.
Passion.
Performance.

