

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : Rolled Steel NEMA Premium
Efficiency Three-Phase

Product code : 12751142

Catalog # : 00536OT3E182T-S

Frame : 182/4T
Output : 5 HP (3.7 kW)
Poles : 2
Frequency : 60 Hz
Rated voltage : 230/460 V
Rated current : 12.6/6.32 A
L. R. Amperes : 96.1/48.0 A
LRC : 7.6x(Code J)
No load current : 6.20/3.10 A
Rated speed : 3510 rpm
Slip : 2.50 %
Rated torque : 7 ft.lb
Locked rotor torque : 190 %
Breakdown torque : 300 %
Insulation class : F
Service factor : 1.15
Moment of inertia (J) : 0.1386 sq.ft.lb

Locked rotor time : 27s (cold) 15s (hot)
Temperature rise : 80 K
Duty cycle : Cont.(S1)
Ambient temperature : -20°C to +40°C
Altitude : 1000 m.a.s.l.
Cooling method : IC01 - ODP
Mounting : F-1
Rotation¹ : Both (CW and CCW)
Noise level² : 65.0 dB(A)
Vibration : A
Starting method : Direct On Line
Approx. weight³ : 58.7 lb
Painting plan : 207N (ISO 12944 - C2)
Color : Munsell N 1 - Matte
Design : B

Output	50%	75%	100%
Efficiency (%)	85.5	86.5	86.5
Power Factor	0.66	0.78	0.85

Foundation loads
Max. traction : 141 lb
Max. compression : 193 lb

	Drive end	Non drive end
Bearing type	6206 ZZ	6205 ZZ
Sealing	Without Bearing Seal	Without Bearing Seal
Lubrication interval	-	-
Lubricant amount	-	-
Lubricant type	Mobil Polyrex EM	

Notes
USABLE @208V 13.5A SF 1.00 SFA 13.5A

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.
- (4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page 1 / 1		
Checked by				
Date	08/10/2026			
		Revision		