QT Pro / Pro+ / Max 5-15 | QT-54

When performance and efficiency are in demand, Quincy's QT Series is the premier industrial piston air compressor. The splash-lubricated QT is built with a cast iron body for strength and durability and an aluminum head for optimal cooling and longevity. The QT delivers lasting value through industry leading performance and reliability.



1. Air Filter
2. Splash-lubricated Piston Pump
3. Oil Level Sight Glass
4. Induction Motor
5. Magnetic Starter
6. Pressure Switch and Gauge
7. Drain Valve
8. Receiver

QT 5-15 HP Reciprocating Air Compressors

The QT Series Is Best For:

- Professional and industrial applications requiring premium efficiency and reliability
- Available with Pro, Pro+ and Max or fully custom configured models
- Aluminum head for optimal heat dissipation and increased life-span
- Optimized valve design for the highest volumetric efficiency in the market

QT MODELS AND CONFIGURATIONS

HP	Phase	Voltage Options	Unit Configuration	Tank Configuration	Tank Size (Gal)	ACFM (Max Pressure)	RPM	Pump Model	Approx Ship Wt. (lbs)	LxWxH (In)
3	1	230	Simplex	Vertical	60	10.8 (100PSI)	1180	QTS-3	290	30x23x68
5	1	230	Simplex	Vertical	60	18.4 (100PSI)	1028	QTS-5	345	31x23x68
5	1	208, 230	Simplex	Vertical	60	15.2 (175PSI)	1350	QT-54	350	31x23x70
					80				417	32x26x69
5	1	208	Simplex	Vertical	80	17.2 (175PSI)	658	QT1	565	35x28x77
				Horizontal					595	67x30x49
		230	Duplex	Horizontal	120	17.2* (175PSI)	658	QT1 (x2)	1115	79x34x54
5	3	200, 460, 575	Simplex	Vertical	80	17.2 (175PSI)	658	QT1	565	35x28x77
				Horizontal					595	67x30x49
			Duplex	Horizontal	120	17.2* (175PSI)	658	QT1 (x2)	1115	79x34x54
7.5	1	208, 230	Simplex	Vertical	80	23.6 (175PSI)	896	QT1	595	35x28x77
				Horizontal					630	67x30x49
		230	Duplex	Horizontal	120	23.6* (175PSI)	896	QT1 (x2)	1180	79x34x54
7.5	3	200, 460, 575	Simplex	Vertical	80	23.6 (175PSI)	896	QT1	595	35x28x77
				Horizontal					630	67x30x49
			Duplex	Horizontal	120	23.6* (175PSI)	896	QT1 (x2)	1180	79x34x54
10S	1	230	Simplex	Vertical	120	27 (165PSI)	1007	QT1	780	37x34x78
				Horizontal					740	71x30x55
			Duplex	Horizontal	200	27* (165PSI)	1007	QT1 (x2)	1555	76x44x63
10S	3	200, 230, 460, 575	Simplex	Vertical	120	29.8 (165PSI)	1192	QT1	780	37x34x78
				Horizontal					740	71x30x55
			Duplex	Horizontal	200	29.8* (165PSI)	1192	QT1 (x2)	1555	76x44x63
10	3	200, 230, 460, 575	Simplex	Vertical	120	36 (175PSI)	682	QT2	945	49x34x78
				Horizontal					890	71x30x55
			Duplex	Horizontal	200	36* (175PSI)	682	QT2 (x2)	2090	76x56x64
15	3	200, 230, 460, 575	Simplex	Horizontal	120	51 (175PSI)	932	QT2	1000	71x30x55
			Simplex	Horizontal	200	51 (175PSI)	932	QT2	1335	76x56x64
			Duplex	Horizontal	200	51* (175PSI)	932	QT2 (x2)	2315	76x56x64

*Performance shown per pump on duplex units

Fuel Type	HP	Engine Brand	Tank Configuration	Tank Size (Gal)	Splash Lubricated Model	ACFM @ 175 psig	RPM
Gas	9	Honda	Horizontal	30	QT-54	14.5	1300
Gas	11	Honda			QT1	18.7	622
	13	Honda				23.6	867
	14	Kohler				23.6	867
Diesel	10	Yanmar				22.0	800



QT Pro Package 5-15 hp

- ODP Motor
- Motor Overload Protection
- Ball Valve Tank Drain
- Automatic Start/Stop 5 to 10 hp
- Dual Control on 15 hp
- NO Bull Extended Warranty Available

QT Max Package 5-15 hp

- ODP Motor
- Motor Overload Protection
- Automatic Tank Drain
- Automatic Start/Stop 5 to 7.5 hp
- Dual Control on 10-15 hp
- Low Oil Level Shutdown
- Air Cooled Aftercooler
- NO Bull Extended Warranty Available
- Isolator pads on horizontals



* Must purchase associated kit at the same time as the compressor to receive warranty extension

QT Pro + 5-15 hp

- ODP Motor
- Motor Overload Protection
- Automatic Tank Drain
- Automatic Start/Stop 5 to 10 hp
- Dual Control on 15 hp
- Low Oil Level Shutdown
- NO Bull Extended Warranty Available

WARRANTY INFORMATION

NO BULL	Optional NO BULL Warranty
	Pro/Pro+/Max Package with Extended Warranty Kit
	3-Year Pump/2-Year Package Warranty
	OEM Parts/Fluids and Online Registration Required

©2026 Quincy Compressor. All rights reserved. QTPro5-15 06-2026